

Cisco Digital Media Suite: Cisco Digital Media Player 4400G

The Cisco® Digital Media Suite (DMS) is a comprehensive offering of webcasting and video sharing, digital signage, and business IPTV applications that can help transform how organizations learn, grow, communicate, and collaborate. Support from the broad Cisco partner ecosystem of deployment, solution-development, and content-creation partners helps ensure a successful digital media implementation.

The Cisco Digital Media Player 4400G (DMP 4400G) is an integrated component of the Cisco Digital Media Suite for Cisco Digital Signs and Cisco Cast.

Cisco Digital Media Player

The Cisco Digital Media Player 4400G (Figure 1) is a highly reliable, IP-based digital media player that handles display and playback of compelling, rich digital media—including high-definition live broadcasts or on-demand video, Flash animations, graphics, text tickers, and other web content—across a network of digital signs.

The Cisco Digital Media Player 4400G is fully manageable as a standalone device; however, as part of the integrated Cisco Digital Signs and Cisco Cast systems, it is a powerful, customizable digital media publishing endpoint. Using the Cisco Digital Media Manager (DMM), the centralized management system component of the Cisco Digital Media Suite, you can easily, flexibly, and remotely publish centralized content to networked digital displays. You can attach the Cisco DMP 4400G to virtually any on-premises digital display at any location—for example, in a branch-office bank, retail store, or a break room or lobby—across any geography.

Figure 1. Cisco Digital Media Player 4400G



The Cisco Digital Media Player 4400G supports sophisticated functions such as touchscreens from ELO Touchsystems, 3M, Zytronic, and General Touch along with 802.11 b/g wireless network connectivity. In addition, the output to displays is fully customizable and can include dynamic playlists; the Cisco Cast program guide; division of screen real estate into multiple addressable regions; high-definition (HD) media playback; and remote management of digital displays - on/off, volume, contrast, and brightness. The Cisco DMP 4400G has a small form factor, weighing less than 4.5 pounds (2 kg) and measuring 10 x 8 x 2 inches (254 x 203 x 51 mm).

Key Features and Benefits

The Cisco Digital Media Player 4400G integrates with the Cisco Digital Media Manager to deliver:

- Standards-based video codec support with MPEG1, MPEG2, and MPEG-4 Part 10, and MP3 audio, all delivered within MPEG-2 TS over User Datagram Protocol (UDP) or RTP over RTSP (RTP over TCP) in both standard- and high-definition (SD and HD, respectively) formats
- Windows Media 9 and VC-1 Audio and Video codec support for on-demand content delivered over HTTP
- Touchscreen support from market leaders ELO Touchsystems, 3M, Zytronic, and General Touch
- Wireless network connectivity over the 802.11 b/g network standard with the following wireless security protocols:
 - Wi-Fi Protected Access (WPA)
 - WPA2
 - Extensible Authentication Protocol-Flexible Authentication via Secure Tunneling (EAP-FAST)
 - Wired Equivalent Privacy (WEP)
- **Flexible, real-time publishing:** You can instantly publish and update content across individual or groups of digital displays, and control and schedule the frequency and duration of content playback (day-parting).
- **Broadcast Cisco Cast:** You can control IP-based broadcast television through the Cisco Digital Media Player Remote Control and on-screen program guide.
- **Low ongoing operational costs and ease of use:** The management interface was designed with the nontechnical user in mind to keep the required level of training low.
- **Speed of deployment:** Simplified IT installations that require little additional network expense reduce the burdens of deployment and maintenance commonly placed on IT.
- **Reliability and power of the network:** Tightly integrated with the network, the Cisco Digital Media Player uses the reliability and security of the underlying network as a platform; this appliance-based solution has no moving parts, avoiding security and maintenance concerns associated with PCs.

Cisco Digital Media Player Remote Control

The Cisco Digital Media Player Remote Control (Figure 2) is a small-form-factor, highly functional device optimized to support interactivity with the Cisco DMP 4305G and DMP 4400G systems. This remote allows you to navigate and select the channels and on-demand videos through the Cisco Cast on-screen program guide.

Figure 2. Cisco Digital Media Player Remote Control



Table 1 lists the innovative features and benefits the Cisco Digital Media Player 4400G offers.

Table 1. Features and Benefits of Cisco Digital Media Player 4400G

Feature	Benefit
MPEG 1, 2, and 4 Part 10 in SD and HD, graphics, web content, Adobe Flash 9 or 10 animation, Windows Media 9 and VC-1, MP3 Audio, and tickers	<ul style="list-style-type: none"> • Support for industry-standard MPEG video formats and web content for a compelling digital media experience • Windows Media 9 and VC-1 support for expanded video-on-demand (VoD) support • Audio-only options with support for MP3 audio format
Local storage of 4-GB capacity	<ul style="list-style-type: none"> • Storage of OS images and content for local playback or failover for greater reliability and robust operation
Touchscreen technology support	<ul style="list-style-type: none"> • Capabilities to support the connecting of touchscreen-enabled displays to your Cisco DMP 4400G to expand your interactive functions
802.11 B/G wireless network support	<ul style="list-style-type: none"> • Flexible Cisco Digital Signs deployments through support for wireless network connectivity; new floor plans and relocation of signs can now be simplified with wireless connectivity
IP-enabled delivery of live broadcasting and on-demand video content	<ul style="list-style-type: none"> • Quick and immediate content changes to react to business needs; no drastic cutover required for organizations moving to a complete IP environment
Remote management of display (on/off, volume, contrast, and brightness)	<ul style="list-style-type: none"> • Ability to control critical digital signage display functions remotely, reducing the need for local operations resources
Full-screen video or division of the screen[*]	<ul style="list-style-type: none"> • Capability to view video or graphics in full-screen mode • Capability to divide displays into separate regions for multiple content playback windows with text, tickers, graphics, and video
Customizable on-screen presentations	<ul style="list-style-type: none"> • Customized interface to reflect an organization's brand
Small form factor: 10 x 8 x 2 in. (254 x 203 x 51 mm); weighs 4.5 lb (2 kg)	<ul style="list-style-type: none"> • Easy to mount to digital displays
15W power consumption (average)	<ul style="list-style-type: none"> • Low power consumption for higher reliability and reduced capital expenditures (CapEx) and operating expenses (OpEx); environmentally friendly
Integration with Cisco Digital Media Suite, Cisco ECDS, Cisco Application and Content Networking System (ACNS), and Cisco Wide Area Application Services (WAAS) products	<ul style="list-style-type: none"> • Flexibility spanning the entire digital media value chain: easily layer on other video applications such as Cisco Show and Share (VoD and live webcasting to the desktop user)

^{*} With the Cisco Digital Media Manager; dependent on chosen display technology

Product Specifications

Tables 2 and 3 give specifications and device manager client requirements, respectively, for the Cisco Digital Media Player 4400G.

Table 2. Cisco Digital Media Player 4400G Product Specifications

Product Parameter	Specification	
Supported protocols	<ul style="list-style-type: none"> • FTP and Secure FTP (SFTP) • HTTP and HTTPS • User Datagram Protocol (UDP) • Real-Time Transport Protocol (RTP) over Real Time Streaming Protocol (RTSP) 	
Video containers	<ul style="list-style-type: none"> • MPEG Transport Stream (TS, TP, TRP, M2T, M2TS, and MTS) • ASF • WMV 	
Video codecs	<ul style="list-style-type: none"> • Video MPEG1 • Video MPEG2: Main Profile at High Level • Video MPEG4 Part 10 Baseline and Main profiles • Video Windows Media 9 and VC-1–VoD only • Aspect ratio: 4:3 and 16:9 • HD (up to 1080p at 16:9) progressive and interlace video resolution • Video data rate up to 28 Mbps • Internal Hardware Decoder delay configurable to < 1 sec 	
Audio codecs	<ul style="list-style-type: none"> • Audio MPEG1 Layers 1 and 2 • MP3 • MPEG4 AAC Low Complexity • AC-3 • Audio data rate: 64–320 kbps 	
Physical connectors	Ethernet copper 10/100/1000BASE-T, RCA Video, S-Video, Mini 3.5-mm Stereo Audio Jack, SPDIF, HDMI, and RS-232 and USB	
	Cable Type	Maximum Supported Cable Length
	Composite or RCA cable	10 ft (2m)
	HDMI 1.1**	16 ft (5m)
	S-Video	10 ft (2m)
	USB 2.0 (2)	15 ft (5m)
Wireless connectivity	SPDIF	10 ft (2m)
	Wireless Radio	Security Protocols
Remote control	802.11 B/G support	WPA, WPA2, EAP-FAST, and WEP
	Transmitter Type	Maximum Supported Distance
Touchscreen support	Infrared (IR)	15 ft (4.57m)
	Vendor	Supported Systems
	3M	Touch Sensor and Systems: <ul style="list-style-type: none"> • 3M MicroTouch ClearTek II touch sensor • 3M MicroTouch System SCT3250CX • 3M MicroTouch Sensor SCT7650 • 3M MicroTouch System SCT3250SX • 3M MicroTouch Capacitive TouchSense System • 3M MicroTouch DST touch system Display Systems: <ul style="list-style-type: none"> • 3M MicroTouch Display M1500SS (15 in.) • 3M MicroTouch Display M1700SS (17 in.) • 3M MicroTouch CT150 15-in. LCD Touch Monitor

Product Parameter	Specification	
		<ul style="list-style-type: none"> • 3M MicroTouch ChassisTouch 17-in. LCD Touch Monitor
	ELO TouchSystems	All Elo TouchSystems touchmonitors and Interactive Digital Signage with IntelliTouch SAW, AccuTouch and CarolITouch touch technologies. Recommended products for digital signage: IDS with IntelliTouch touch technology
	Zytronics	Zybrid Screen systems
	General Touch	All systems supported by the ST6001S controller
Functional	Video in: <ul style="list-style-type: none"> • MPEG1, MPEG2, MPEG4 Part 10, Windows Media 9, and VC-1 Audio in: <ul style="list-style-type: none"> • Transport stream: Up to 6 audio packet IDs (part numbers) in transport stream • MP3 Video out: <ul style="list-style-type: none"> • Analog video (composite and S-Video) • Digital video (HDMI 1.1) Audio out: <ul style="list-style-type: none"> • Analog unbalanced audio (mono and stereo) • MPEG1 Layer 2: Selected; packet IDs in transport stream (1 of 6) MPEG4 AAC and AC-3 <ul style="list-style-type: none"> • Selected elementary audio (1 of 6) 	
Power	Input voltage: <ul style="list-style-type: none"> • 12V Input current: <ul style="list-style-type: none"> • 3 ADC Power consumption: <ul style="list-style-type: none"> • Peak: 30W; average: 15W 	
Flash memory	<ul style="list-style-type: none"> • 4-GB CF-card with endurance of 1,000,000 write/erase cycles for OS images and application storage 	
Environmental	Operating temperature: <ul style="list-style-type: none"> • 41 to 104°F (5 to 40°C) • Passed 500-hour test of the uninterrupted video playback in 125.6°F (52°C) dry-heat environment Humidity: <ul style="list-style-type: none"> • 20 to 80% noncondensing 	

* Cable quality can be a factor.

** An HDMI extender product can be used to extend the cable to 150 ft.

Table 3. Cisco Digital Media Player 4400G Device Manager Client Requirements

Component	Requirements
Browser	Windows <ul style="list-style-type: none"> • Internet Explorer 6.0 or later, or Firefox 1.5 or later recommended Linux or UNIX <ul style="list-style-type: none"> • Firefox 1.5 through 3.0 recommended Apple Macintosh <ul style="list-style-type: none"> • Firefox 1.5 through 3.0 recommended

Ordering Information

Table 4 provides ordering information for the Cisco Digital Media Player 4400G.

Table 4. Cisco Digital Media Player 4400G Ordering Information

Product Name	Part Number
Cisco Digital Media Player 4400G Note: Includes Cables Accessory Kit	DMP-4400G-53-K9
Digital Signage User Lic. for DMP 4400G	DMP-4400G-SW53-K9
Cisco Digital Media Player Remote Spare	DMP-RM-K9=
Digital Media Player V5-V5.1 Perptl. SW Upgrade	DMP-SW53-U-K9
Spares	
Cisco Digital Media Player 4400G, Cables Accessory Kit, Spare Note: A Cables Accessory Kit is already included with the Cisco Digital Media Player 4400G. This Spare Kit is an additional cost.	DMP4400-ACC-KIT
Cisco Digital Media Player Remote Spare	DMP-RM-K9=

Cisco Services

Cisco and our partners provide a broad portfolio of intelligent, personalized services and support that can help you realize the full value of your video investment, increase business agility and network availability. This portfolio of services drives business transformation through a network-based collaboration platform that enables business to collaborate anywhere, anytime. For more information about these services, visit:

<http://www.cisco.com/go/services/digitalmedia>.

For More Information

For more information about the Cisco Digital Media Suite, visit <http://www.cisco.com/go/dms> or contact your local Cisco account representative.



Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)