

**Professional**

Advanced HD Network Bullet Camera

DN-16064**EAN 4016032301899**

High Resolution - For a crisp view of the smallest details

Feeling safe is priceless. For this reason you should never compromise on security. Do we not have enough worries these days? Hand a part over: This camera is ideal for reliable outdoor monitoring. The camera is IP67-conform and withstands wind and weather. The H.264 video standard ensures smooth, crystal clear images at a lower network load compared to legacy technologies. Thanks to infrared lighting in the dark the camera automatically switches to night mode. The megapixel sensor is inspiring: superior image quality and highest definition show even the tiniest detail. Not only the hardware is convincing: With auto motion detection and supplied software your equipment is future-proof and you save a lot of time! Just focus on the essential instead of painstakingly going through the daily recordings! Video images are only generated in case of activity. Even automatic face recognition is possible!

- True Day and Night surveillance
- Large aperture lens (F1.8)
- Optical Zoom lens: f4.0mm - f9.0mm
- Smart Zoom: Zoom on the object that triggered the alarm
- Viewing Angle: 75° - 36°
- Weatherproof IP67 outdoor design with cable management
- High resolution and best video performance
- Enhanced motion detection and alarm notification functions
- Alarm and event notification by FTP and Email
- Powerful mobile surveillance supporting iPhone, Blackberry and WinCE devices
- Low-latency video streaming with H.264 compression format
- LAN Speed: 10/100Base-TX Ethernet
- Supported Protocols: DDNS, PPPoE, DHCP, NTP, SNTP, TCP/IP, ICMP, SMTP, FTP, HTTP, RTP, RTSP
- Frame Rate NTSC: 30, PAL: 25
- Number of Online Users: 10
- Security: Multiple user access levels with password protection
- Management by web browser or CMS software for up to 16 network cameras control simultaneously
- Compatible to the future proof ONVIF Standard
- Image Sensor: 1/3" 1.3 Megapixel HR color MOS sensor
- Resolution: 1280x1024 pixel NTSC / PAL
- Min Illumination 0.3 Lux / F1.8
- Shutter Speed 1/60 (1/50) to 1/100,000 sec.
- IR effective distance up to 40 meters with 56 IR LEDs
- Smart Light Control for optimal brightness, contrast and exposure results
- IP Rating 67
- Operating Temperature: -20°C - 40°C
- Power Source (±10%): AC100V ~ 240V
- Dimensions (mm): 282.4(L) x 117.89(W) x 212.63(H)



**Professional**