

EcoTank L6580

BRINGING THE COMBINED POWER OF QUALITY, FUNCTIONALITY AND SPEED

Cut through demanding workloads with the EcoTank L6570 and L6580 colour printers. High print speeds of up to 25 ipm[^] and the all-in-one capability enable seamless printing, copying and scanning of office documents without any delays. Print letterheads, envelopes and even engineering drawings at the finest quality with Epson's DURABrite ET inks. Print using WiFi Direct from any smart device, or print using the intuitive 10.9 cm (4.3") touchscreen to make your office printing effortless.











Page Yield







Warranty²





EcoTank L6570



Ш





Each printer comes bundled with a star kit of 4 bottles of Epson genuine inks.



Epson's Heat-Free Technology

*The total Colour CPP including

black ink is 48 paise.

An innovation that cuts the heat out of office printing. As a result, you save time, money, power and the environment.

DURABrite ET Pigment Ink

Specially-formulated pigment ink that achieves long-lasting, razor-sharp and water-resistant prints.


Epson Warranty for Peace of Mind

Enjoy warranty coverage of one year or 200,000 prints, whichever comes first.

ECOTANK L6570 / L6580



MODEL NUMBER L6570 L6580 Printer Type Print, Scan, Copy, Fax with ADF Printing Printing Technology PrecisionCore™ Printhead Nozzle Configuration 800 x 1 nozzles each (Black, Cvan, Magenta, Yellow) Bi-directional printing Print Direction Maximum Resolution 4800 x 2400 dpi Minimum Ink Droplet Volume 3.8 pl Draft Text - Memo, A4 (Black#1 / Colour#2) Up to 32 ppm / 32 ppm ISO 24734, A4 (Black / Colour) Simplex: Up to 25.0 ipm / 25.0 ipm | Duplex: Up to 21 ipm / 21 ipm First Page Out Time (Black / Colour), A4 Simplex: Up to 5.5 sec / 5.5 sec | Duplex: Up to 11.0 sec / 11.5 sec Photo Default - 10 x 15 cm / 4 x 6" *2 #3 (Border / Borderless) Approx. 26 sec per photo (Border / Borderless) ESC/P-R, ESC/P Raster ESCP-R / ESCP-Raster, PCL and Post Script Printer Language Yes (Up to A4) Copying Copy Speed ISO 29183, A4 (Black / Colour), Flatbed Simplex: Up to 23.0 ipm / 23.0 ipm ISO 24735, A4 (Black / Colour), ADF Simplex: Up to 22.5 ipm / 22.5 ipm | Duplex: Up to 19.0 ipm / 19.0 ipm Maximum Copies from Standalone 999 copies 25 - 400% Reduction/Enlargement Maximum Copy Resolution 600 x 600 dpi Maximum Copy Size Legal Scanner Type Flatbed colour image scanner Sensor Type CIS 1200 x 2400 dpi Optical Resolution Maximum Scan Area (Flatbed and ADF) Flatbed: A4, Letter | ADF: Up to legal Scanner Bit Depth Colour 48-bit input, 24-bit output Grayscale 16-bit input, 8-bit output Black & White 16-bit input, 1-bit output Scan Speed (A4 | Flatbed / ADF) Monochrome 200 dpi Flatbed: 5 sec | ADF (Simplex / Duplex): Up to 27.5 ipm / 11 ipm Colour 200 dpi Flatbed: 10 sec | ADF (Simplex / Duplex): Up to 9.0 ipm / 6.0 ipm Fax Function Type of Fax Walkup B/W & Colour Fax, PC Fax Receive Memory / Page Memory 6 MB, Page memory up to 550 pages Error Correction Mode FAX Speed (Data Transfer Rate) Up to 33.6 kbps, Approx. 3 sec/page FAX Resolution Up to 200 x 200 dpi Transmission Paper Size Flatbed ADF Α4 Receiving Paper Size Half Letter, A5, B5, A4, Letter, Legal Speed Dial / Group Dial Up to 200 numbers, 199 groups Fax Features PC Fax (Transmission/Receive), Automatic Redial, Address book, Broadcast Fax (Mono Only), Transmit Reservation, Polling Reception, Fax Preview, Memory reception, Fax to Email, Fax to Folder, Automatic 2-sided Fax ADF Function Support Paper Thickness 64-95 g/m² Paper Capacity 50 sheets Card Slot / USB Host Function Type of Direct Printing USB Memory Paper Handling Paper Feed Method Number of Paper Trays THREE (2-Front Cassette, 1-Rear Feeder) Paper Hold Capacity Input Capacity Cassette1: 250 sheets; Cassette 2: 250 sheets; Rear feeder: 50 sheets Output Capacity 125 sheets Paper Size A4, Letter, Legal B4, B5, A5, B6, A6, 8.5 x 13", 5 x 7", 4 x 6", 8 x 10", Legal (8.5 x 14"), 16:9 wide, Envelopes: #10, DL, C6, C4 Maximum Paper Size 215.9 x 6000 mm Print Margin 3 mm top, left, right, bottom via custom settings in printer driver Interface USB USB 2.0 Network Ethernet, WiFi IEEE 802.11b/g/n, WiFi Direct Network Protocol TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, BOOTP, APIPA, PING, DDNS, mDNS, SNTP, SLP, WSD, LLTD Network Management Protocols Mobile and Cloud Printing Epson iPrint, Epson Email Print, Remote Print Driver, Scan to Cloud Epson Connect Other Mobile Solutions Apple AirPrint™, Mopria Print Service Control Panel 10.9 cm (4.3") Colour LCD Touchscreen LCD Screen Printer Software Software Support Enson ScanSmart Windows XP / Vista / 7 / 8 / 8.1 / 10, Windows Server 2003 / 2008 / 2012 / 2016 / 2019 Operating System Compatibility Mac OS X 10.6.8 or later Electrical Specifications Rated Voltage AC 220 - 240 V Rated Frequency 50 - 60 Hz Power Consumption Operating 19.0 W Standby 9.1 W 0.8 W Sleep 0.2 W Power off Noise Level PC Printing/ Plain Paper Default* Sound Power: 6.6 db(A) / Sound Pressure: 51 db(A) Consumables Page Yield " Order Code C13T06G198 Black Ink Bottle 7,500 C13T06G298 Magenta Ink Bottle 6 000 (Composite Yield) C13T06G398 C13T06G498 Yellow Ink Bottle C12C934601



EcoTank L6580 Weight & Dimensions Weight: 17.8 kg (39.2 lbs)

(16.7")

(13.8") 500 mm (19.7") 425 mm

"Print speed (Pages Per Minute) is calculated when printed on A4 plain paper in the fastest mode, 10 x 15 cm photo print speed when printed on Epson Premium Glossy Photo Paper. Print speed may vary depending on system configuration, print mode, document complexity, software, type of paper used and connectivity. Print speed does not include processing time on host computer.







#2 Black text and graphics

(4 x 6") 2 Glossy paper drying time is minimum 24 hours as the

inks used are pigment-based.

3 Default mode in accordance with ISO7779 for MFPs

4 Quoted yields are based on the ISO 24711/24712 patterns of mixed text and colour graphics with Epson methodology. Quoted yields are based on the replacement ink bottles purchased. For print quality, part of the ink from the included bottles is used for printer startup so vields could be lower than those of replacement ink bottles. Actual yields will vary due to reasons including images printed, print settings, temperature and humidity. Yields may be lower when printing infrequently or predominantly with one ink colour. lnk is used for both printing and printhead maintenance. All inks are used for both black and colour printing.

©2020 Epson India Pvt, Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation. All other product names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Information correct as of October 2020

EPSON INDIA PVT. LTD.

12th Floor, The Millenia, Tower A, No.1, Murphy Road, Ulsoor, Bangalore 560 008. Tel: 080-4566 5000, Fax: 080-4566 5005.

Regional Offices:

Ahmedabad 3314 8500/01, Chennai 3967 7500, Cochin 4012 315, Coimbatore 98942 19200, Kolkata 4603 4729, Mumbai 3079 8200, New Delhi 3312 0300, Pune 3028 6000/05, Hyderabad 4857 0032, Jaipur 78699 11699.



